



SERIE 252 ■

PNEUMATIC COUPLINGS
PNEUMATISCHE KUPPLUNGEN



UNIVERSAL COUPLING

Interchangeability - Kompatibilität
TST 026, RECTUS 25, RECTUS 26, CEJN 320,
and
PARKER PEF, JWL 520, JWL 530, Legris
RECTUS 23, FORSTER, CEJN 310, US MIL STD.
4109 1/4", HANSEN 3000, PARKER LEGRIS
1/4, TST 024 ATLAS COPCO QIC 08, ISO 6150 B
and
TST 022, RECTUS 14, RECTUS 22, ARO 210,
PARKER 50, CEJN 300, ORION 44510, JWL
522, JWL 532

Temperature Range - Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508 PSI)


Flow capacity - Nennweite
NW - 7.8

Option - Optionen
F - Straight through flow -
ungehinderter Durchfluss
S - Stainless Steel - Edelstahl
V - Viton Seal - Viton Dichtung


Material - Material

- Coupler Body-
Kupplungsgrundkörper : Brass Nickel Plated -
Messing vernickelt
- Back Part -
Hinterteil : Steel Nickel Plated -
Stahl vernickelt
- Sleeve - Hülse : Steel Nickel Plated -
Stahl vernickelt
- Valve - Ventil : Brass - Messing
- Springs - Federn : Stainless Steel -
Edelstahl
- Locking O-Ring -
Sprengring : Stainless Steel -
Edelstahl
- Balls - Kugeln : Stainless Steel -
Edelstahl AISI 420
- Seals - Dichtungen : Nitrile (Ni) - NBR (Ni)


Couplers and Plugs
Kupplungen und Nippel



Male Thread Coupling
Kupplung mit Aussengewinde



Female Thread Coupling
Kupplung mit Innengewinde



Standard Hose Barb Coupling
Kupplung mit Schlauchtülle

Connection
Anschlüsse

Order No
Bestellnr.

SW

L

ØD

BSPT 1/4"	252 RG 13	19	60	23
BSPT 3/8"	252 RG 17	19	60	23
BSPT 1/2"	252 RG 21	22	60	23

BSP 1/4"	252 DG 13	19	55	23
BSP 3/8"	252 DG 17	19	55	23
BSP 1/2"	252 DG 21	24	57	23

6 mm - 1/4"	252 HG 06	19	71	23
8 mm - 5/16"	252 HG 08	19	71	23
9 mm - 5/14"	252 HG 09	19	71	23
10 mm - 3/8"	252 HG 10	19	71	23
13 mm - 1/2"	252 HG 13	19	71	23