



SERIE 253

PNEUMATIC COUPLINGS
PNEUMATISCHE KUPPLUNGEN



SUPER FLOW **SUPERDURCHFLUSS** (2000 NI/min)

Interchangeability - Kompatibilität
TST 026, RECTUS 25, RECTUS 26, CEJN 320,
PARKER PEF, JWL 520, JWL 530, Legris
and
TST 022, RECTUS 14, RECTUS 22, ARO 210,
PARKER 50, CEJN 300, ORION 44510, JWL
522, JWL 532

Temperature Range - Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508 PSI)


Flow capacity - Nennweite
NW - 7.8

Option - Optionen
F - Straight through flow -
ungehinderter Durchfluss
S - Stainless Steel - Edelstahl
V - Viton Seal - Viton Dichtung


Material - Material

- Coupler Body-
Kupplungsgrundkörper : Brass Nickel Plated -
Messing vernickelt
- Back Part -
Hinterteil : Steel Nickel Plated -
Stahl vernickelt
- Sleeve - Hülse : Steel Nickel Plated -
Stahl vernickelt
- Valve - Ventil : Brass - Messing
- Springs - Federn : Stainless Steel -
Edelstahl
- Locking O-Ring -
Sprengling : Stainless Steel -
Edelstahl
- Balls - Kugeln : Stainless Steel -
Edelstahl AISI 420
- Seals - Dichtungen : Nitrile (Ni) - NBR (Ni)


Couplers and Plugs
Kupplungen und Nippel



Male Thread Coupling
Kupplung mit Aussengewinde



Female Thread Coupling
Kupplung mit Innengewinde



Standard Hose Barb Coupling
Kupplung mit Schlauchtülle

Connection
Anschlüsse

Order No
Bestellnr.

SW

L

ØD

BSP 1/4"	253 EG 13	19	59,3	23
BSP 3/8"	253 EG 17	19	60,5	23
BSP 1/2"	253 EG 21	22	54,5	23

BSP 1/4"	253 DG 13	19	54,3	23
BSP 3/8"	253 DG 17	19	54,3	23
BSP 1/2"	253 DG 21	24	56,3	23

6 mm - 1/4"	253 HG 06	19	70,3	23
8 mm - 5/16"	253 HG 08	19	70,3	23
9 mm - 5/14"	253 HG 09	19	70,3	23
10 mm - 3/8"	253 HG 10	19	70,3	23
13 mm - 1/2"	253 HG 13	19	70,3	23