


PNEUMATIC COUPLINGS
PNEUMATISCHE KUPPLUNGEN


SERIE 026B

DOUBLE SHUT OFF **BEIDSEITIG ABSPERRBAR**




Couplers and Plugs
Kupplungen und Nippel

Connection Anschlüsse | Order No Bestellnr. | SW | L | ØD




Male Thread Coupling
Kupplung mit Aussengewinde

BSP 1/8"	026 EGB 10	21	40,3	24,7
BSP 1/4"	026 EGB 13	21	41,3	24,7
BSP 3/8"	026 EGB 17	21	41,3	24,7
BSP 1/2"	026 EGB 21	21	44,3	24,7
M 14x1,5	026 EGBM 14	21	42,3	24,7
M 16x1,5	026 EGBM 16	21	42,3	24,7
M 18x1,5	026 EGBM 18	21	42,3	24,7




Female Thread Coupling
Kupplung mit Innengewinde

BSP 1/8"	026 DGB 10	21	39,3	24,7
BSP 1/4"	026 DGB 13	21	41,3	24,7
BSP 3/8"	026 DGB 17	21	41,3	24,7
BSP 1/2"	026 DGB 21	24	44,3	24,7
M 14x1,5	026 DGBM 14	21	40,3	24,7
M 16x1,5	026 DGBM 16	21	40,3	24,7
M 18x1,5	026 DGBM 18	21	40,3	24,7




Standard Hose Barb Coupling
Kupplung mit Schlauchtülle

6 mm - 1/4"	026 HGB 06	21	55,3	24,7
8 mm - 5/16"	026 HGB 08	21	55,3	24,7
9 mm - 5/14"	026 HGB 09	21	55,3	24,7
10 mm - 3/8"	026 HGB 10	21	55,3	24,7
13 mm - 1/2"	026 HGB 13	21	55,3	24,7




Plastic Hose Coupling
Kupplung für Kunststoffschlauch

6 x 8 mm - M 12x1	026 PGB 06	21	46,3	24,7
8 x 10 mm - M 16x1	026 PGB 08	21	49,3	24,7
9 x 12 mm - M 16x1	026 PGB 09	21	49,3	24,7



Plastic Hose Coupling With Spring
Kupplungen für Kunststoffschlauch mit Knickschutzfeder

6 x 8 mm - M 12x1	026 YGB 06	21	127	24,7
8 x 10 mm - M 16x1	026 YGB 08	21	145	24,7
9 x 12 mm - M 16x1	026 YGB 09	21	145	24,7



Panel Mount Standard Hose Coupling
Kupplung mit Schottverschraubung Schlauchanschluss

6 mm - M 12x1	026 MGB 06	21	63,3	24,7
8 mm - M 16x1	026 MGB 08	21	63,3	24,7
10 mm - BSP 1/4"	026 MGB 10	21	63,3	24,7

Interchangeability - Kompatibilität
TST 025B, RECTUS 25KB, RECTUS 26KB

Temperature Range - Temperaturbereich
-20°C +100°C (-4°F +212°F)

Working Pressure - Betriebsdruck
0 - 35 bar (0 - 508 PSI)

Flow capacity - Nennweite
NW - 7.2

Option - Optionen

- K - Chrome Plated - verchromt
- KN - Chemical Nickel Plated - chemisch vernickelt
- N - Nickel Plated - vernickelt
- S - Stainless Steel - Edelstahl (S3:AISI 303, S6:AISI 316TI)
- V - Viton Seal - Viton Dichtung

For optional orders please add the symbol of your option end of the order no. Bei Optionsbestellungen Kennbuchstabe bitte hinzufügen (Beispiel: 026 EGB 13-K-V)

Material - Material

- Coupler Body- Kupplungsgrundkörper : Brass - Messing
- Back Body - Hinterteil : Brass Nickel Plated - Messing vernickelt
- Sleeve - Hülse : Steel Nickel Plated - Stahl vernickelt
- Valve - Ventil : Brass - Messing
- Springs - Federn : Stainless Steel - Edelstahl
- Locking O-Ring - Sprengling : Stainless Steel - Edelstahl
- Balls - Kugeln : Stainless Steel - Edelstahl AISI 420
- Seals - Dichtungen : Nitrile (Ni) - NBR (Ni)
- Plug - Nippel
- Plug Profile -Stecker Profil: Brass Nickel Plated - Messing vernickelt
- Back Body - Hinterteil : Brass Nickel Plated - Messing vernickelt
- Valve - Ventil : Brass Nickel Plated - Messing vernickelt
- Spring - Federn : AISI 301
- Seal - Dichtungen : Nitrile (Ni) - NBR (Ni)

