



→ Dimensions

A (mm)	140	240	340
	440	540	
D (mm)			
E (mm)			
F (mm)			
G (mm)			
H (mm)			
I (mm)			
L (mm)			
Capacity (kg)			

Material to be conveyed

Specify presence of lubricant, coolant or other fluid, if present.

→ Standard features

DRIVE UNIT

- Position: LH side
- Speed: 4,5 m/min fixed
- Voltage: 400 V / 50 Hz
- With ON/OFF switch

BELT

- Smooth green PU covering (ref. Pantone 320)
- Vulcanized belt joint
- Heat-welded slats h 30 mm pitch 400 mm
- Operating temperature: -10 °C to +90 °C

→ Notes

→ Options

BELT

High grip PVC	+ slats h	<input type="text"/>	mm pitch	<input type="text"/>
Smooth PU	+ slats h	<input type="text"/>	mm pitch	<input type="text"/>
Smooth PU	+ spondaflex h 30 mm +			
slats h 20 mm	pitch	<input type="text"/>		

CONTROL PANEL

- INVERTER:** adjustable speed from to m/min
- PAUSE/WORK:** timed run and stop
- PULSE:** timed run activated by voltage-free external signal
- FEEDER:** run and stop controlled by voltage-free external signal

DRIVE UNIT

Mounted on opposite side: RH side

UNLOADING CHUTE / SEPARATOR

Standard unloading chute

Single-roller separator mod. N-SRS

Spiral-roller separator mod. N-FSRV

