



→ Dimensions

A (mm)

B (mm)

H (mm)

Capacity (kg)

Material to be conveyed

Specify presence of lubricant, coolant or other fluid, if present.

→ Standard features

DRIVE UNIT

- Position: LH side
- Speed: 5,8 m/min fixed
- Voltage: 400 V / 50 Hz
- With ON/OFF switch

BELT

- Smooth green PU covering (ref. Pantone 320)
- Vulcanized belt joint
- Operating temperature: -10 °C to +90 °C

→ Notes

→ Options

DRIVE UNIT

- Mounted on opposite side: RH side
- Mounted under the belt
- Drum motor (drive roller)

SPECIAL BELTS

Smooth green PU covering (ref. Pantone 320) with slats
 h = mm (standard 20/30/50),
 pitch = mm (standard 400)

For high temperature
 (max 110 °C, with momentary peaks up to 130 °C)
 High grip, green PVC (ref. Pantone 320)

SUPPORTS

- Wheels with brake (standard)
- Anti-vibration feet
- Anti-vibration feet + Wheels
- WITHOUT legs

SIDE PANELS

- STANDARD side panels h = 80 mm
- WITHOUT side panels
- Special side panels:

CONTROL PANEL

- INVERTER: adjustable speed from to m/min
- PAUSE/WORK: timed run and stop
- PULSE: timed run activated by voltage-free external signal
- FEEDER: run and stop controlled by voltage-free external signal

SPECIAL HEADINGS

- Idle roller diam. 50 mm
- Idle roller diam. 20 mm